

Sept. 8, 1931.



M. KIRSCH

1,822,659

MEANS FOR EXTRACTING AIR FROM WATER

Filed July 5, 1928

2 Sheets-Sheet 1



INVENTOR.
Michael Kirsch
BY
Erwin Wheeler & Woolard
ATTORNEYS

Sept. 8, 1931.

M. KIRSCH


1,822,659

MEANS FOR EXTRACTING AIR FROM WATER

Filed July 5, 1928

2 Sheets-Sheet 2

Fig. 3.



UNITED STATES PATENT OFFICE

MICHAEL KIRSCH, OF MILWAUKEE, WISCONSIN

MEANS FOR EXTRACTING AIR FROM WATER

Application filed July 5, 1928. Serial No. 290,317.

My invention relates to an improvement in means for extracting air from water.

The object of my invention is to provide means for renewing the supply of oxygen in submarine vessels or in any compartment where oxygen is needed and wherein the atmosphere is being vitiated of its supply of oxygen.

In the drawings:

Figure 1 is a vertical section through my air renewing device showing a fragmentary section of the wall of a submarine vessel in which my device may be utilized.

Figure 2 is a section on line 2-2 of Figure 1.

Figure 3 is a view of the top of my device showing a portion thereof broken away to indicate the method of mounting and driving various parts.

Figure 4 is a transverse section through the dispersing tank 13, and showing a portion of the bottom of the tank 13 broken away to exhibit the oppositely rotatable fans.

Like parts are identified by the same reference characters throughout the several views.

I am aware that means for renewing the air in submarines have heretofore been provided, however, I have found that a device constructed according to the disclosure hereinafter set forth is much more efficient of operation and actually supplies more available oxygen to a compartment containing

function in connection with my device, in the order in which the various parts function upon water introduced through the pipe 11, these three units are as follows:

First, a container 13 comprising side walls in any desired shape and a perforated bottom 14. In the specific structure shown in Figure 1 I have shown a tubular insert 15 through which a power shaft 16 may pass for the transmission of power from above the container 13 to a point below the container where a second unit of my device is installed.

Below the perforated bottom 14 of the container 13 the second unit of my structure is constructed. This unit comprises a set of oppositely rotatable propellers or fans 17 and 18, one of these fans 17, being mounted for rotation directly upon the shaft 16 and the other 18, being mounted for opposite rotation upon a hub or sleeve 19, power being transmitted to said sleeve 19 through gears 20, 21 and 22, gear 22 in turn being mounted upon a power shaft 23 driven through bevel gears or otherwise from a motor 24 as shown at 25.

Surrounding the propellers or fans 17 and 18, I provide a perforated shield 26 which has no bottom and which is, therefore, formed in the shape of a perforated cylinder mounted upon a bracket 27 secured to the side wall 13 of the first receiving unit described above.

The third and last unit of my device a

forated bottom of said container where the fans 17 and 18 revolving oppositely under the power transmitted from the motor 24 through gears 37 and 38 at the top of my device and through gears 20, 21, and 22 through shaft 16 and sleeve 19, respectively, disperse the drops of water in the form of mist. These fans swirl the drops of water outwardly ultimately against the perforated cylinder 26 through which a constant spray is induced and from which finely divided particles of water pass into the atmosphere into the main compartment 10.

The atmosphere of the main compartment 10 is maintained at a slightly reduced pressure by reason of the operation of the evacuating fan 28 with a result that all oxygen extracted or impacted from the water by the re-